

Report of JPL ITRS Combination Center

presented by
Richard S. Gross

Jet Propulsion Laboratory
California Institute of Technology
Pasadena, CA 91109–8099, USA

International Earth Rotation and Reference Systems Service
Directing Board Meeting No. 65

December 9, 2017
New Orleans, Louisiana

© 2017 California Institute of Technology. Government sponsorship acknowledged.

Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not constitute or imply its endorsement by the United States Government or the Jet Propulsion Laboratory, California Institute of Technology.

JTRF2014 Updates

Towards More Frequent Terrestrial Reference Frame Updates

Claudio Abbondanza¹, Toshio M Chin¹, Richard S Gross¹,
Michael B Heflin¹, Jay W Parker¹, Benedikt S Soja¹,
Xiaoping Wu¹,

December, 11 2017

¹ Jet Propulsion Laboratory - California Institute of Technology


Why Would TRF Updates Be Useful?

- ITRF official products are **released at intervals of 3-to-5 years** (see <http://itrf.ensg.ign.fr/>)
- **Frame Obsolescence**, i.e. frame degradation with time [see e.g. Blewitt, 2015]
 - **TRFs do not age well:**
 - Quakes, equipment changes at ITRF sites introduce station position discontinuities and degrade the frame quality
 - 3-to-5 years in between ITRF releases acceptable (?) tradeoff (new releases are **burdersome** and somehow prohibitive for the analyses centers, IGS/GNSS in particular, because of the entire reprocessing of an ever-increasing dataset)
 - **Frequent Frame Updates** instead of frequent ex-novo (and impractical) Frame releases might alleviate obsolescence.

Why Would TRF Updates Be Useful?

- To maintain the accuracy of ITRF-like terrestrial frames by updating them as new data become available.
- To maintain the consistency of the Earth Orientation Parameters (EOPs) with the updated terrestrial frames (EOPs get assimilated as well when updating the TRF).
- To provide updates to the time series of geocentre motion (CM-CN) based on the assimilation of new data.

Global Space-Geodetic Network




Global Space-Geodetic Networks adopted in our proof of concept
(495 Stations with Observing History > 2.5 years)


Dataset and Combination Setup

Dataset	SNX Files from IGS, IVS, ILRS, IDS for ITRF2014
Network	495 Stations
Frame Type	Time Series
Model	Trend, Annual
Process Noise	Station-Dependent Random Walk
Origin	Quasi-Instantaneous CM (SLR)
Scale	Quasi-Instantaneous SLR/VLBI
Orientation	No-Net-Rotation to ITRF2008


Combination Tests For our Proof of Concept



Scatterplots of the WRMS Differences (Pred/Upd - Truth)



GNSS Station at Iquique (Chile) – Updates




Black dots are position observations, whereas red solid lines are KALREF-derived. Solid green vertical lines mark position offsets. Light red-shaded envelopes represent 1- σ error bars.

Correlations in Ground Deformation


Correlation Coefficients: GRACE and other data

GRACE equivalent water with atmos/ocean loading restored:




Last panel: GFZ surface fluid loading model data (Dill and Dobslaw 2013)
⇒ Some long-distance correlations may be noisy/inconsistent.



APL+CWS+OBP



GRACE



GFZ-u



Joint TRF / CRF / EOP Determination



AGU Fall Meeting, New Orleans, LA, USA – December 11, 2017


A two-level approach to VLBI terrestrial and celestial reference frames using both least-squares adjustment and Kalman filter algorithms

Benedikt Soja^{1*}, H. Krasna², J. Böhm², R. Gross¹,
C. Abbondanza¹, T. Chin¹, M. Heflin¹, J. Parker¹, X. Wu¹

*bsoja@jpl.nasa.gov

¹ Jet Propulsion Laboratory, California Institute of Technology, Pasadena, United States of America

² Technische Universität Wien, Vienna, Austria



Jet Propulsion Laboratory
California Institute of Technology

New concept for terrestrial reference frames

DTRF2014

- Least-squares adjustment
- Input: normal equations
- Secular frame
- Optional loading displacement time series

[Seitz et al., 2016]

JTRF2014

- Kalman filter + smoother
- Input: station coordinates + covariances
- Time series frame

[Abbondanza et al., 2017]

New concept

- Least-squares adjustment
- Normal equations
- Secular frame
- Optional Kalman filter time series based on residuals of secular frame

New concept for celestial reference frames

ICRF2

- Least-squares adjustment
- Input: normal equations
- Constant frame

[Fey et al., 2015]

Kalman filter CRF

- Kalman filter + smoother
- Input: station coordinates + covariances
- Time series frame

[Soja et al., 2017]

New concept

- Least-squares adjustment
- Normal equations
- Constant frame
- Optional Kalman filter time series based on residuals of constant frame

Realizing the new concept

1. Single-session analysis to create normal equations
2. Computation of **secular** frames (global solution)
 - NNT/NNR w.r.t. DTRF2014 and NNR w.r.t. ICRF2
 - Two TRF solutions: linear & linear + annual + semi-annual
3. Apply secular frames in single-session analysis to estimate station and source coordinates
 - Residuals w.r.t. secular frames
4. Feed residuals into Kalman filter and smoother to create **time series** consistent with secular frame
 - 6-parameter transformation to DTRF2014
 - 3-parameter rotation to ICRF2




VLBI data

- 1980 – 2016.5
- 5446 IVS-VLBI sessions
- **Secular frame**
 - 136 VLBI stations (22 used for datum definition)
 - 4097 radio sources (1178 used for datum definition)
 - Seasonal signals: only estimated for datum stations
- **Time series frame**
 - 119 VLBI stations
 - 822 radio sources




TRF solution examples

Algonquin Park, radial component




TIGO Concepción, East component



CRF solution examples

0119+115 (defining), declination



4C 39.25 (special handling), right asc.

